

MANAGING ORACLE TABLE PARTITIONING IN PEOPLESOFT APPLICATIONS WITH GFC_PSPART PACKAGE

Prepared By David Kurtz, Go-Faster Consultancy Ltd.

Technical Manual

Version 1.04 – http://www.go-faster.co.uk/gfc_pspart.manual.pdf

Thursday 20 October 2011

(E-mail: david.kurtz@go-faster.co.uk, telephone +44-7771-760660)

File: gfc_pspart.manual.v1.04.doc, 20 October 2011

Contents

Introduction.....	3
Delivered Files	4
Installation.....	5
Operation.....	6
Example Output	8
Meta-Data.....	11
Meta-data Tables.....	12
GFC_PART_INDEXES.....	12
GFC_PART_LISTS	13
GFC_PART_TABLES.....	14
GFC_PART_RANGES.....	17

GFC_PART_RANGE_LISTS.....	18
GFC_PS_IDXDDLPARM.....	18
GFC_PS_INDEXDEFN.....	19
GFC_PS_KEYDEFN.....	20
GFC_TEMP_TABLES.....	21
Working Storage Tables.....	22
GFC_PS_TABLES.....	22
GFC_PS_TAB_COLUMNS.....	23
GFC_ORA_TAB_COLUMNS.....	24
GFC_DDL_SCRIPT.....	24
Context.....	25
Example Meta-Data.....	27
Example General Ledger Meta-Data.....	28
Example Global Payroll Meta-Data.....	31
Global Indexes.....	37
Global Payroll Streams.....	38
Function Based Indexes.....	39
List Partitioning.....	41
Selectively Building Sub-Partitions.....	43
Setting Context Values.....	44
Globally Partitioned Indexes.....	44
Example Time & Labor Meta-Data.....	45
Archiving Time-Based Range Partitioning.....	45
Meta-Data Report.....	47
Partitioned Tables.....	47
Range Partitioning.....	47
List Partitioning.....	48
Global and Globally Partitioned Indexes.....	49
Specified Tablespaces.....	49
Package GFC_PSPART.....	51
BANNER Procedure.....	51
DISPLAY_DEFAULTS Procedure.....	52
HISTORY Procedure.....	53
RESET_DEFAULTS Procedure.....	54
SET_DEFAULTS Procedure.....	54
TRUNCATE_TABLES Procedure.....	56
SPOOLER Function.....	57
MAIN Procedure.....	58

Introduction

This document is a guide to the PeopleSoft Partitioning utility package; GFC_PSPART.

Although table partitioning is usually presented as performance option for Data Warehouse systems, it can also be used very successfully in OLTP systems such as PeopleSoft. Even official PeopleSoft documentation such as the Red Paper '*PeopleSoft 8 Batch Performance on Oracle Database*' discusses the merits of partitioning¹. However, that paper completely fails to mention that PeopleSoft's Application Designer will not build the DDL to build partitioned objects. If you want to partition tables in your application, you are on your own facing the prospect of manually maintaining DDL scripts.

The GFC_PSPART PL/SQL package dynamically generates the DDL to create and manage partitioned and Global Temporary tables and indexes in PeopleSoft systems based on the meta-data in the PeopleTools tables and additional meta-data that describes the partitioning strategy. These generated scripts replace the use of the Application Designer to build DDL scripts.

Partitioning can also be a segue into archiving. Older historical data in separate partitions can be archived by dropping the partition or changing it with another table (and possibly exchanging it again into another partition). GFC_PSPART can suppress generation of partitions that have been archived and generate a partitioned copy of a partitioned table with only the partitions necessary to hold archived data.

If you are partitioning output tables to prevent read-consistency contention between concurrent processes, then temporary working storage tables must also be addressed. However, rather than partition them it is an option to make them Global Temporary tables. The GFC_PSPART package can also generate the DDL for this.

Essentially, GFC_PSPART can be considered to be a replacement for the build script builder in Application Designer for PeopleSoft records that are to be built as Partitioned and Global Temporary tables.

¹ However, this document doesn't properly explain the advantages of partitioning. The reduction in I/O can be achieved by:

- i. Partition elimination to reduce scans of tables and indexes.
- ii. Separation of data to reduce consistent read during parallel batch processing..

Delivered Files

The package is written in PL/SQL. It is composed of a number of SQL scripts. The scripts are designed to run in Oracle's SQL*Plus utility only. It is not supported to use any other tool.

gfcbuildpkg.sql: This script installs the package.

- calls *gfcbuildtab.sql*,
- builds the package header – the package header has not been wrapped and the parameters to the public procedures and functions in the package are documented here.
- runs *gfcbuildpkgbody.plb* to create the package
- Sets default values in a database context

gfcbuildtab.sql: This script contains the DDL to build the working storage tables used by the package.

gfcbuildpkgbody.plb: The GFC_PSPART package has been supplied as a 'wrapped' package. The source code is not available.

partdata.sql: The GFC_PSPART package is almost entirely driven by meta-data. Most of it comes from the PeopleTools tables, but the definition of which tables to partition, how they should be partitioned, how their indexes should be partitioned, and where those partitions should be built is. Partitioning configuration on some systems can become quite complicated. Separate scripts to build meta-data for each functional area have been created (such as *gp-partdata.sql*) and are called from this script. This script also generates a summary report of the partitioning meta-data after it has been loaded (see Appendix Example Meta-Data from page 27).

gp-partdata.sql: This utility was originally developed for use with PeopleSoft Global Payroll Systems where Payroll 'Streaming²' is in use. This file builds the meta-data for the partitioning of Global Payroll tables only. The configuration required is almost identical for most customers so a standard configuration is supplied as a starting point. It is expected that this will then be customised as necessary.

ppm-partdata.sql: From PeopleTools 8.48 LONG columns can be replaced with CLOBs. This script builds the meta-data to specify partitioning for the tables used by PeopleSoft Performance Monitor to store performance metrics. This can significantly improve the performance of analytics queries. This script is supplied as an example.

gfcbuild.sql: Is a script to reload the partitioning meta-data, call the GFC_PSPART package and spool the output to file (see Operation on page 6).

² PeopleSoft coined this term to describe running certain payroll processes in several concurrently executing processes.

gfcbuildone.sql: This is a variant of *gfcbuild.sql* which builds the DDL scripts for named tables only (see Operation on page 6).

gfcbuildspool.sql: This script spools the output of the GFC_PSPART package from a temporary working storage table to a file. This approach was used so that the package can be run by a developer from a client PC.

Installation

All the files should be placed in the same directory.

If running on a windows client, you may experience problems if there is a space character in the path to this directory. SQL scripts may not be able to execute other SQL scripts. The workaround is make that directory the working directory in the shortcut to SQL*Plus. It can be helpful to have a dedicated SQL*Plus shortcut in the working directory.

The working storage tables and the package can be installed by running the *gfcbuildpkg.sql* script (which in turn calls *gfcbuildtab.sql* and *gfcbuildpkgbody.plb*)

The package should be installed and executed by the owner of the PeopleSoft database – usually SYSADM. This account must be explicitly granted the following privileges rather than via a role by running *gfcbuildpriv.sql*:

SELECT ON sys.v_\$version – some aspects of generated SQL vary with the version of Oracle. For example, from Oracle 10g the DROP TABLE statements can optionally include the PURGE option.

SELECT ON sys.v_\$parameter

CREATE ANY CONTEXT – the package uses a context rather than a database table to hold settings persistently that modify its behaviour. This privilege is only required temporarily during installation, and can be revoked again afterwards.

SELECT ON sys.dba_tables – the package checks which table already exist by querying this catalogue view.

SELECT ON sys.dba_tab_partitions – the package checks which table partitions already exist by querying this catalogue view.

SELECT ON sys.dba_ind_partitions – the package checks which index partitions already exist by querying this catalogue view.

Operation

The delivered scripts *gfcbuild.sql* and *gfcbuildone.sql* demonstrate how the package can be used to rebuild all or most tables.

Essentially this process is a replacement for building DDL scripts in Application Designer. The main procedure builds the DDL and puts it into the working storage table and the spools it out to a number of files. The procedure can be run for all tables, or for some tables. It can be run several times for different tables to build up a single set of scripts which handle a specified list of tables.

```
rem gfcbuild.sql
rem (c) Go-Faster Consultancy Ltd.
clear screen

spool gfcbuild

execute gfc_pspart.truncate_tables(p_all=>TRUE);3
@@partdata4
--execute gfc_pspart.truncate_tables;5

--all tables
execute gfc_pspart.main;6

--just generate global temporary tables
--execute gfc_pspart.main(p_rectype => 'T');7

--just generate named tables
--execute gfc_pspart.main(p_recname => 'GP_PI_GEN_SOVR', p_rectype => 'P');8

--extract script to file
@@gfcbuildspool.sql9
```

³ All the meta-data and working storage tables are being truncated. It is only necessary to do this if the meta-data has changed and therefore needs to be reloaded.

⁴ The *partdata.sql* script (see Example Meta-Data on page 27) reloads the meta-data. Other meta-data scripts are called from within this script.

⁵ It is only necessary to run *truncate_tables* on the working storage tables if it has not already been run to clear all tables.

⁶ Running the main procedure with no parameters builds the DDL for ALL tables specified in the meta-data.

⁷ It is possible to build the DDL just some tables, this commented out command would build

⁸ This command generates the DDL for a specified partitioned table.

⁹ Finally, the generated DDL is spooled from the working storage table to a local file. This approach is used so that the utility can be used on a client rather than just a database server.

set head on feedback on termout on pages 50

This is an alternative version of gfcbuild.sql that is only going to build the DDL for a number of named tables.

```
rem gfcbuildone.sql
rem (c) Go-Faster Consultancy Ltd.
clear screen

spool gfcbuild

--execute gfc_pspart.truncate_tables(p_all=>TRUE);10
--set termout off
--@@partdata
--set termout on
execute gfc_pspart.truncate_tables;11

--just generate named tables
--execute gfc_pspart.main(p_recname => 'GP_RSLT_ACUM', p_rectype => 'P');
--execute gfc_pspart.main(p_recname => 'GP_RSLT_PIN', p_rectype => 'P');
execute gfc_pspart.main(p_recname => 'GP_RSLT%', p_rectype => 'P');12
execute gfc_pspart.main(p_recname => 'TL_PAYABLE_TIME', p_rectype => 'P');
execute gfc_pspart.main(p_recname => 'TL_RPTD_TIME');
execute gfc_pspart.main(p_projectname => 'GFC_PROJECT');13

--pause
--extract script to file
@@gfcbuildspool.sql
```

¹⁰ In this case the meta-data is not being truncated and reloaded, because it has not changed.

¹¹ Instead, we will only truncate the working storage tables.

¹² In this case all tables whose names begin with GP_RSLT. This is an alternative to explicitly listing them.

¹³ In this case, the DDL for all the records that appear in the named project for which there is also partition meta-data will be generated. The package still generates an output project with the name specified in the context (see Context on page 22).

If you run the main procedure for a record that has already been generated since you last cleared the working storage tables, you will generate a unique constraint error.

```
SQL> execute gfc_pspart.main(p_recname => 'GP_PI_GEN_SOVR');

PL/SQL procedure successfully completed.

SQL> execute gfc_pspart.main(p_recname => 'GP_PI_GEN_SOVR');
BEGIN gfc_pspart.main(p_recname => 'GP_PI_GEN_SOVR', p_rectype => 'P'); END;

*
ERROR at line 1:
ORA-00001: unique constraint (SYSADM.GFC_PS_TABLES) violated
ORA-06512: at "SYSADM.GFC_PSPART", line 334
ORA-06512: at "SYSADM.GFC_PSPART", line 3467
ORA-06512: at line 1
```

Example Output

This is an example of the script generate by the package.

```
spool gfcbuild_hcm89_t1_payable_time.lst14
REM Generated by GFC_PSPART - (c)Go-Faster Consultancy Ltd. www.go-faster.co.uk 2001-2010
REM HCM89 @ 13:09:58 02.10.201015
...
WHENEVER SQLERROR CONTINUE16
ALTER TABLE sysadm.ps_t1_payable_time RENAME PARTITION t1_payable_time_001 TO old_t1_payable_time_001;
...
DROP INDEX ps_t1_payable_time;
...
WHENEVER SQLERROR EXIT FAILURE
CREATE TABLE sysadm.gfc_t1_payable_time
(emplid VARCHAR2(11) NOT NULL
...
)
TABLESPACE GPAPP
PCTUSED 95 PCTFREE 1
PARTITION BY RANGE(EMPLID)
(PARTITION t1_payable_time_001 VALUES LESS THAN ('KUL451') TABLESPACE GPSTRM01TAB
...
,PARTITION t1_payable_time_010 VALUES LESS THAN (MAXVALUE) TABLESPACE GPSTRM10TAB
)
```

¹⁴ A spool file is generated for each table processed within each generated script, thus there is a detailed log of what has been performed by the generated scripts.

¹⁵ This comment shows the name of the PeopleSoft database against which the script was generated, and the date and time at which it was generated.

¹⁶ The scripts are designed to be run in SQL*Plus. They use the WHENEVER SQLERROR command to control whether SQL*Plus terminates after a SQL error in a command. Thus the script is failsafe, and can be left to run unattended. It may error, but it will never destroy data because it continues to execute after an error.

```

ENABLE ROW MOVEMENT
PARALLEL
NOLOGGING
/

GRANT SELECT ON sysadm.gfc_tl_payable_time TO gfc_read_only
/
GRANT INSERT, UPDATE, DELETE ON sysadm.gfc_tl_payable_time TO gfc_update
/

LOCK TABLE sysadm.ps_tl_payable_time IN EXCLUSIVE MODE
/

CREATE OR REPLACE TRIGGER sysadm.tl_payable_time_nochange17
BEFORE INSERT OR UPDATE OR DELETE ON sysadm.ps_tl_payable_time
BEGIN
    RAISE_APPLICATION_ERROR(-20100,'NO DML OPERATIONS ALLOWED ON SYSADM.PS_TL_PAYABLE_TIME');
END;
/

ALTER TABLE sysadm.ps_tl_payable_time PARALLEL
/
LOCK TABLE sysadm.ps_tl_payable_time IN EXCLUSIVE MODE18
/

BEGIN
INSERT /*+APPEND NOLOGGING*/ INTO sysadm.gfc_tl_payable_time (
) SELECT ...
FROM sysadm.ps_tl_payable_time;
COMMIT;
END;
/
...
CREATE UNIQUE INDEX sysadm.gfc_tl_payable_time ON sysadm.gfc_tl_payable_time
(emplid
,empl_rcd
,dur DESC
,seq_nbr
)
LOCAL
(PARTITION tl_payable_time_001 TABLESPACE GPSTRM01IDX
...
,PARTITION tl_payable_time_010 TABLESPACE GPSTRM10IDX
)
TABLESPACE PSINDEX
PCTFREE 1
PARALLEL

```

¹⁷ A trigger is created on the table being copied to prevent any updates occurring between now and when the new copy replaces it. This will, quite deliberately, cause any attempted updates to fail. It will not prevent direct path inserts, but PeopleSoft doesn't do this.

¹⁸ The source table is explicitly locked in case any transactions were in flight when the trigger was created.

```
NOLOGGING
/

ALTER INDEX sysadm.gfc_tl_payable_time
LOGGING
/
ALTER INDEX sysadm.gfc_tl_payable_time
NOPARALLEL
/

WHENEVER SQLERROR CONTINUE
DROP INDEX sysadm.ps_tl_payable_time
/
WHENEVER SQLERROR EXIT FAILURE
ALTER INDEX sysadm.gfc_tl_payable_time RENAME TO ps_tl_payable_time19
/

WHENEVER SQLERROR EXIT FAILURE
ALTER TABLE sysadm.gfc_tl_payable_time LOGGING NOPARALLEL MONITORING
/
WHENEVER SQLERROR CONTINUE
ALTER TABLE sysadm.ps_tl_payable_time RENAME TO old_tl_payable_time
/

WHENEVER SQLERROR EXIT FAILURE
ALTER TABLE sysadm.gfc_tl_payable_time RENAME TO ps_tl_payable_time
/

WHENEVER SQLERROR CONTINUE
DROP TABLE sysadm.old_tl_payable_time PURGE
/

ALTER TRIGGER T_LOCK ENABLE
/

DROP TRIGGER sysadm.tl_payable_time_nochange
/
```

¹⁹ The newly created objects replace the old ones through a series of rename operations, and the old objects are dropped.

A P P E N D I X

Meta-Data

Not surprisingly, there is nowhere in the PeopleTools tables to hold partitioning information, so additional tables have been created. It is necessary to understand what the meta-data that in tables means, so that you can specify your own meta-data.

Meta-data Tables

GFC_PART_INDEXES

This table can be used to specify any indexes that are not to be locally partitioned. Any indexes for which there is no entry in this table will be locally partitioned.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
INDEXID*	VARCHAR2(1)	NOT NULL	Identifier of PeopleSoft Index
PART_ID	VARCHAR2(8)	NOT NULL	ID of partitioning strategy. Many tables can share one partitioning strategy.
PART_COLUMN	VARCHAR2(100)	NOT NULL	Range partitioning column, or comma separated columns.
PART_TYPE	VARCHAR2(1)	NOT NULL, R, L, H or N	Partitioning Type: (R)ange or (L)ist (H)ash, or (N)ot partitioned
SUBPART_TYPE	VARCHAR2(1)	L, H, N	Subpartitioning Type: (L)ist or (H)ash. Default: (N)ot sub-partitioned
SUBPART_COLUMN	VARCHAR2(100)		Name of column on which to sub-partition.
HASH_PARTITIONS	NUMBER	NOT NULL >= 0	Number of Hash partitions. Default 0
IDX_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at index level.
IDX_STORAGE	VARCHAR2(100)		Storage Clause to be specified at index level.
OVERRIDE_SCHEMA	VARCHAR2(30)		Schema in which table to be built. Used if not building object in schema of PeopleSoft Owner ID.

NAME_SUFFIX	VARCHAR2(20)	Suffix to be added to Index and partition names
-------------	--------------	---

GFC_PART_LISTS

This table specifies the list partition definitions. It contains one row for each list partition defined.

Column	Datatype	Null / Constraint	Description
PART_ID*	VARCHAR2(8)	NOT NULL	ID of partitioning strategy. Many tables can share one partitioning strategy.
PART_NO*	NUMBER	NOT NULL	Controls Sequence List Partition specification in DDL
PART_NAME	VARCHAR2(30)	NOT NULL	This value is appended to the RECNAME name to make the partition name
LIST_VALUE	VARCHAR2(100)	NOT NULL	List partition values.
TAB_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at table partition level.
IDX_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at index partition level.
TAB_STORAGE	VARCHAR2(100)		Storage Clause to be specified at table partition level.
IDX_STORAGE	VARCHAR2(100)		Storage Clause to be specified at index partition level.

Additional Unique Constraint: PART_ID, PART_NAME

GFC_PART_TABLES

This table contains one row for each record whose corresponding database table is to be partitioned.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
PART_ID	VARCHAR2(8)	NOT NULL	ID of partitioning strategy. Many tables can share one partitioning strategy.
PART_COLUMN	VARCHAR2(100)	NOT NULL	Range partitioning column, or comma separated columns.
PART_TYPE	VARCHAR2(1)	NOT NULL, R, L or H	Partitioning Type: (R)ange or (L)ist or (H)ash only
SUBPART_TYPE	VARCHAR2(1)	L, H, N	Subpartitioning Type: (L)ist or (H)ash. Default: (N)ot Partitioned
SUBPART_COLUMN	VARCHAR2(100)		Name of column on which to sub-partition.
HASH_PARTITIONS	NUMBER	NOT NULL >= 0	Number of Hash partitions. Default 0
TAB_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at table level.
IDX_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at index level.
TAB_STORAGE	VARCHAR2(100)		Storage Clause to be specified at table level.
IDX_STORAGE	VARCHAR2(100)		Storage Clause to be specified at index level.
STATS_TYPE	VARCHAR2(1)	Y, N, D	Y: Collect statistics D: Delete Statistics N: Do Not Collect Statistics
SAMPLE_SIZE	NUMBER		As sample size in DBMS_STATS, except that NULL indicates that DBMS_STATS.AUTO_SAMPLE_SIZE will be used.

METHOD_OPT	VARCHAR2(100)		Passed to METHOD_OPT parameter of DBMS_STATS procedures
OVERRIDE_SCHEMA	VARCHAR2(30)		Schema in which table to be built. Used if not building object in schema of PeopleSoft Owner ID
CRITERIA	VARCHAR2(1000)		Complete WHERE clause with logical condition that will appended to the INSERT ... SELECT statement that copies data from original table into new table ²⁰ .
ARCH_FLAG	VARCHAR2(1)	A, N, D	Enable archiving feature A=Archive N=Do not archive Note that partitions will only be archived if both this flag and GFC_PART_RANGES.ARCH_FLAG are set.
ARCH_SCHEMA	VARCHAR2(30)		Schema in which the archive table is to be built. Explicit SELECT privilege will be granted to the PeopleSoft Owner ID
ARCH_RECNAME	VARCHAR2(15)		Record name to be used to determine name of archive table. If null the table name will be determined by ARCH_TABLE_NAME. To be used if the archive table is to be created in the PeopleSoft Owner's schema.
ARCH_TABLE_NAME	VARCHAR2(30)		Name of Archive Table. If null, the archive table will have the same name as the base table.
NOARCH_CONDITION	VARCHAR2(1000)		<i>Logical condition to identify the rows that should be moved back the table after they have been exchange out during the archive process.</i> <i>This column is not used by the wrapped package.</i>

²⁰ This parameter can be used when you want to archive data and also reorganise the partitioned tables.

Other Constraints:

PART_COLUMN and SUBPART_COLUMN may not both be null

The type of partitioning may not be the same as the sub-partitioning

GFC_PART_RANGES

This table specifies the range partition definitions. It contains one row for each range defined.

Column	Datatype	Null / Constraint	Description
PART_ID*	VARCHAR2(8)	NOT NULL	ID of partitioning strategy. Many tables can share one partitioning strategy.
PART_NO*	NUMBER	NOT NULL	Sequence Number of range partition
PART_NAME	VARCHAR2(30)	NOT NULL	This value is appended to the RECNAME name to make the partition name
PART_VALUE	VARCHAR2(100)	NOT NULL	Range less than value for partition
TAB_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at table partition level.
IDX_TABLESPACE	VARCHAR2(30)		Tablespace to be specified at index partition level.
TAB_STORAGE	VARCHAR2(100)		Storage Clause to be specified at table partition level.
IDX_STORAGE	VARCHAR2(100)		Storage Clause to be specified at index partition level.
ARCH_FLAG	VARCHAR2(1)	A, D, N	N=Do Not Archived (default) A=Archive D=Drop Partition Note that partitions will only be archived if both this flag and GFC_PART_TABLES.ARCH_FLAG are set.

Additional Unique Constraint: PART_ID, PART_NAME

GFC_PART_RANGE_LISTS

It is assumed that in a RANGE-LIST partitioned table all combinations should be built. But this may not always be the case. Where a combination is not to be built, a row with a can be added to this table with the value for BUILD set to N.

Column	Datatype	Null / Constraint	Description
PART_ID*	VARCHAR2(8)	NOT NULL	ID of partitioning strategy. Many tables can share one partitioning strategy.
RANGE_NAME	VARCHAR2(30)	NOT NULL	Name of Range partition in GFC_PART_RANGES
LIST_NAME	VARCHAR2(30)	NOT NULL	Name of List partition in GFC_PART_LISTS
BUILD	VARCHAR2(1)	NOT NULL	(Y)es - default (N)o.

GFC_PS_IDXDDLPARM

It is not possible to define function based indexes in PeopleSoft. Sometimes it is also necessary to build such indexes on partitioned tables, and sometimes to partition them. This table is used to specify the DDL override information that would otherwise come from the PeopleTools table PSIDXDDLPARM.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
INDEXID*	VARCHAR2(1)	NOT NULL	Identifier of PeopleSoft Index
PARAMNAME*	VARCHAR2(8)	NOT NULL	Name of DDL Model Parameter
PARAMVALUE	VARCHAR2(128)	NOT NULL	Value to be substituted into DDL model.

GFC_PS_INDEXDEFN

A working storage table that contains details of both the indexes defined in the meta-data for this package and in PeopleTools. Meta-data can be inserted into this table directly if it is necessary to define indexes that are not defined in PeopleSoft. For example, function based indexes.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
INDEXID*	VARCHAR2(1)	NOT NULL	Identifier of PeopleSoft Index
SUBRECNAME	VARCHAR2(15)	NOT NULL	Subrecord from which field definition derived.
SUBINDEXID	VARCHAR2(1)	NOT NULL	Identifier of PeopleSoft Index on subrecord
PLATFORM_ORA	NUMBER	NOT NULL	=1 if index to be build on Oracle datbaase
CUSTKEYORDER	NUMBER	NOT NULL	= 1 if Custom Key Order
UNIQUEFLAG	NUMBER	NOT NULL	= 1 if index to be build unique

GFC_PS_KEYDEFN

It is not possible to define function based indexes in PeopleSoft. Sometimes it is also necessary to build such indexes on partitioned tables, and sometimes to partition them. This table is used to specify the keys on such indexes that would otherwise come from the PeopleTools table PSKEYDEFN.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
INDEXID*	VARCHAR2(1)	NOT NULL	Identifier of PeopleSoft Index
KEYPOSN*	NUMBER	NOT NULL	Posititon of Field within Key
FIELDNAME	VARCHAR2(100)	NOT NULL	Name of Column, or expression.
ASCDESC	NUMBER	NOT NULL	1=Ascending 0=Descending

Additional Unique Constraint: RECNAME, INDEXID, FIELDNAME

GFC_TEMP_TABLES

This table specifies the PeopleSoft record whose corresponding tables are to be built as Oracle Global Temporary Tables. If a PeopleSoft Temporary Record is specified (rectype=7) then all the instances, both shared and non-shared, will be built as Global Temporary Tables.

Column	Datatype	Null / Constraint	Description
RECNAM*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name

Working Storage Tables

A number of other tables are used by the package for working storage

GFC_PS_TABLES

This table holds one row for each record to be generated by the package.

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
TABLE_NAME	VARCHAR2(30)	NOT NULL	Database Table name (of shared record if PeopleSoft Temporary Record)
TABLE_TYPE	VARCHAR2(1)		P = Partitioned Table T = Global Temporary Table
RECTYPE	NUMBER		PeopleSoft Record Type from PSRECDEFN.REC_TYPE 0 = Regular Table 7 = Temporary Table
TEMPTBLINSTANCES	NUMBER		Number of Instances of PeopleSoft Temporary Table
OVERRIDE_SCHEMA	VARCHAR2(30)		Name of Schema in which to build table.
MATCH_DB	VARCHAR2(30)		Y = No difference detected between definition of Table and Partitioning between PeopleSoft and Oracle Catalogues

GFC_PS_TAB_COLUMNS

Column	Datatype	Null / Constraint	Description
RECNAME*	VARCHAR2(15)	NOT NULL	PeopleSoft Record Name
FIELDNAME	VARCHAR2(18)	NOT NULL	PeopleSoft Field Name, which becomes Oracle column name.
USEEDIT	NUMBER	NOT NULL	From PSRECFIELD. Used to define automatically generated Key and Alternate search key indexes in PeopleSoft, and whether DATE and LONG columns are NOT NULL.
FIELDNUM	NUMBER	NOT NULL	Position of field in record, equivalent to position of column in table
SUBRECNAME	VARCHAR2(15)	NOT NULL	Subrecord from which field definition derived ²¹ .

²¹ Because the GFC_PSPART package was originally developed on PeopleTools 8.1, it does not rely on PSRECFIELDDB to be accurate, although it is maintained by Application Designer from PeopleTools 8.4. Instead, it works from PSRECFIELD.

GFC_ORA_TAB_COLUMNS

This table is an extract from USER_TAB_COLUMNS of the required tables to improve performance of the package.

Column	Datatype	Null / Constraint	Description
TABLE_NAME*	VARCHAR2(30)	NOT NULL	Database Table Name
COLUMN_NAME*	VARCHAR2(30)	NOT NULL	Database Column Name
COLUMN_ID	NUMBER	NOT NULL	Database Column ID in table

Additional Unique Constraint on TABLE_NAME, COLUMN_ID

GFC_DDL_SCRIPT

This table holds the DDL commands generated by the package

Column	Datatype	Null / Constraint	Description
TYPE	NUMBER	NOT NULL	Script type. Corresponds with p_type parameter on SPOOLER function (see page 57) 0 = gfcbuild script. Similar to a PeopleSoft Alter by Recreation script 1 = gfcindex: Rebuild All indexes 2 = gfcstats: Refresh All statistics 3 = gfcalter: All missing partitions
LINE_NO	NUMBER	NOT NULL	Line Number of Script
LINE	VARCHAR2(4000)		Line of DDL Script

Context

The *gfc_pspart* package uses a system context, also called *gfc_pspart* to persistently hold certain settings.

Context Variable	Default Value	Description
CHARDEF	N	Use VARCHAR2 character definition.
LOGGING	N	If set to N, DDL script includes NOLOGGING options when building tables and indexes
PARALLEL	Y	Set to Y to include parallel index build option
ROLES	N	Set Y if roles are to be granted to tables
SCRIPTID	GFCBUILD	ID string to be used in name of script and name of project generated.
UPDATE_ALL	PS_UPDATE_ALL	Role to be granted to permanent tables
READ_ALL	PS_READ_ALL	Role to be granted to permanent tables
DROP_INDEX	Y	If set to Y index dropped before rename, else if set to N index is renamed to OLD_
PAUSE	N	Add pause commands to generated script
EXPLICIT_SCHEMA	Y	Explicitly specify PeopleSoft owner ID in DDL script.
BLOCK_SAMPLE	Y	Specify block sampling in update statistics script.
BUILD_STATS	N	If set to Y add gather statistics commands to build script.
DELETETEMPSTATS	Y	If set to Y delete and from Oracle 10g also lock statistics on temporary tables.
LONGTOCLOB	N	If set to Y always create long columns as CLOB, other only do so if PSOPTION.DATABASE_OPTIONS=2
DDLTRIGGER	NULL	Name of DDL trigger to disable at start of script and reenable on completion.
DROP_PURGE	Y	Add purge option to DROP TABLE commands on Oracle 10g or higher.
FORCEBUILD	Y	Debug option only – not supported
DESC_INDEX	Y	If N do not include DESC keyword on columns specified in PeopleSoft as

descending.

Example Meta-Data

Every customer who uses this package has meta-data that is specific to their environment. This is done by providing custom versions of the partdata.sql and other meta-data scripts. partdata.sql contains various pieces of sample meta-data that have been commented out as an example of how to define partitioning for additional tables.

Example General Ledger Meta-Data

The partitioning requirements for General Ledger report provide a good example of some of the things that can be done with this utility.

Here the PS_LEDGER table will be range partitions into temporal partitons by range partitioning on the combination of FISCAL_YEAR and ACCOUNTING_PERIOD. There will be month partitions for fiscal year 2006, quarterly for 2005, and annual partitions prior to that.

Comments in the script have been added using footnotes.

```

INSERT INTO gfc_part_tables (recname, part_id, part_column, part_type, subpart_type, hash_partitions,
tab_tablespace, idx_tablespace, tab_storage, idx_storage, stats_type, sample_size, method_opt)
VALUES('LEDGER', 'GL', 'FISCAL_YEAR,ACCOUNTING_PERIOD'22, 'R', 'LEDGER', 0, 'GLLARGE', 'PSINDEX',
'PCTUSED 90 PCTFREE **PCTFREE**'23, 'PCTFREE **PCTFREE**', 'Y', NULL, 'FOR ALL COLUMNS SIZE 1', NULL);

INSERT INTO gfc_part_ranges24 VALUES('GL',2000,' 2000', '2001,0', NULL25, NULL, 'PCTFREE 0', 'PCTFREE 0'26);
INSERT INTO gfc_part_ranges VALUES('GL',2001,2001, '2002,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2002,2002, '2003,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2003,2003, '2004,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2004,2004, '2005,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');

INSERT INTO gfc_part_ranges VALUES('GL',2005.0, '2005_BF', '2005,1', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2005.03, '2005_Q1', '2005,4', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2005.06, '2005_Q2', '2005,7', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2005.09, '2005_Q3', '2005,10', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2005.12, '2005_Q4', '2005,999', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2005.99, '2005_CF', '2006,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');

INSERT INTO gfc_part_ranges VALUES('GL',2006.0, '2006_BF', '2006,1', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.01, '2006_M01', '2006,2', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.02, '2006_M02', '2006,3', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.03, '2006_M03', '2006,4', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.04, '2006_M04', '2006,5', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.05, '2006_M05', '2006,6', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.06, '2006_M06', '2006,7', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.07, '2006_M07', '2006,8', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.08, '2006_M08', '2006,9', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.09, '2006_M09', '2006,10', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.10, '2006_M10', '2006,11', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.11, '2006_M11', '2006,12', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.12, '2006_M12', '2006,999', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');
INSERT INTO gfc_part_ranges VALUES('GL',2006.99, '2006_CF', '2007,0', NULL, NULL, 'PCTFREE 0', 'PCTFREE 0');

```

²² The table will be range partitioned on the combination of FISCAL_YEAR and ACCOUNTING_PERIOD. Two columns, but partitioned in a single dimension.

²³ By using **PCTFREE**, the value for PCTFREE will come from the value specified in the PeopleSoft meta data from the override value on the object if specified, otherwise from the default on the DDL model.

²⁴ A row is created in GFC_PART_RANGES for each range partition.

²⁵ Tablespaces have not been specified at range partition level, so all partitions will go into the tablespaces specified at TABLE and INDEX level.

²⁶ However, the value for PCTFREE has been overridden on historical partitions that hold data for previous years GL data. This data will not be changed, so it is not necessary to preserve free space in each block. This minimises the number of block reads necessary to access the object.

This is an example of how to build a function based index on a table, and then to partition that index, in this case locally partition.

```
-----  
INSERT data to generate the function based indexed  
-----
```

```
INSERT INTO gfc_ps_idxddlparm (RECNAME,INDEXID,PARMNAME,PARMVALUE)27  
VALUES ('LEDGER','Z','LEDGER','Z', 1, 0, 0);
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',1,'FISCAL_YEAR');
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',2,'ACCOUNTING_PERIOD');
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',3,'CASE WHEN BUSINESS_UNIT LIKE ''XXX%'' AND LEDGER = ''USXXX''  
THEN ''USXXX'' ELSE LEDGER END'); 28
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',4,'DEPTID');
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',5,'ACCOUNT');
```

```
INSERT INTO gfc_ps_keydefn VALUES ('LEDGER','Z',6,'BUSINESS_UNIT');
```

²⁷ Additional index data is added to gfc_ps_idxddlparm.

²⁸ A record is required in gfc_ps_keydefn for each column or expression in the index definition. The expression in the third key is used in many reports, so it makes sense to build a function based index on it, but it still leads on FISCAL_YEAR and ACCOUNTING_PERIOD, and so is also locally partitioned

Example Global Payroll Meta-Data

Some of scripts to build the meta-data for Global Payroll is presented here as an example, with comments and explanations in footnotes. This script is fairly standard for all Global Payroll customers who run their payroll processes streamed.

```

REM gp-partdata.sql
-----
--view to identify country extention tables
-----
CREATE OR REPLACE VIEW gfc_installed_gp29 AS
SELECT  recname,
        rectype,
        CASE SUBSTR(r.recname,1,5)
...
            WHEN 'GPGB_' THEN i.INSTALLED_GP_UK
            WHEN 'GPIE_' THEN i.INSTALLED_GP_IRL
...
            ELSE 'Y'
        END AS installed_gp
FROM    psrecdefn r
,       ps_installation i
WHERE   r.rectype IN(0,7) --only SQL tables can be partitioned or rebuilt as GTTS
;
...

```

Most of the temporary tables listed here are in the Payroll Calculation process (GPPDPRUN). If payroll is run streamed multiple concurrent processes will share the same tables leading to significant read consistency contention. By converting these tables to Oracle Global Temporary Tables, each session, and therefore each process, will have its own physical copy of each table.

The lists of tables are partly static and partly dynamically generated from PeopleTools and Application meta-data.

```

-----
--insert data to describe temporary tables
--country specific tables for installed country extentions only will be added
-----
INSERT INTO gfc_temp_tables
SELECT  r.recname
FROM    gfc_installed_gp r
WHERE   r.installed_gp != 'N'
AND     r.rectype IN(0,7) --only normal tables can be partitioned
AND     (r.recname IN( /*payroll calculation work tables*/
                    'GP_CAL_TS_WRK',
                    'GP_CANC_WRK',
                    'GP_CANCEL_WRK', /*new in 8.4*/

```

²⁹ This view is used to work out which Global Payroll country extentions are installed. Only country specific result tables for installed country extentions will be partitioned or converted to Global Temporary Tables.

```

'GP_DB2_SEG_WRK', /*new in 8.4*/
'GP_DEL_WRK',
'GP_DEL2_WRK', /*new in 8.4*/
'GP_EXCL_WRK',
'GP_FREEZE_WRK', /*new in 8.4*/
'GP_HST_WRK',
'GP_JOB2_WRK', /*13.2.2008*/
'GP_MSG1_WRK', 'GP_MSG3_WRK',
'GP_NEW_RTO_WRK',
'GP_OLD_RTO_WRK',
'GP_PI_HDR_WRK',
'GP_PYE_HIST_WRK', /*13.2.2008*/
'GP_PYE_HIS2_WRK', /*13.2.2008*/
'GP_PYE_ITER_WRK', /*new in 8.4*/
'GP_PYE_ITR2_WRK', /*new in 8.4*/
'GP_PYE_RCLC_WRK', /*new in hcm9.0 - added 21.5.2008*/
'GP_PYE_STAT_WRK',
'GP_PYE_STA2_WRK', /*13.2.2008*/
'GP_RTO_CRD_WRK', /*20.2.2008*/
'GP_RTO_PRC_WRK',
'GP_RTO_TRG_WRK1', /*new in 8.4*/
'GP_RTO_TRGR_WRK',
'GP_SEG_WRK',
'GP_TLPTM_WRK',
'GP_TLSNT_WRK',
'GP_TLTRC_WRK',
'GP_TL_PIGEN_WRK',
'GP_TL_PIHDR_WRK',
'GP_TL_TRG_WRK',
/*pin packager*/
'GP_PKG_ELEM_WRK',
/*GL*/
'GP_ACC_LINE_STG', --added 5.3.2009
'GP_GL_AMT1_TMP', 'GP_GL_AMT2_TMP',
'GP_GL_DATA_TMP',
'GP_GL_DNF_TMP',
'GP_GL_MAPI_TMP',
'GP_GL_OLD_TMP',
'GP_GL_SEG_TMP',
'GP_GL_SEGV_TMP',
'GP_GL_STO6_TMP',
'GP_GL_S7N8_TMP',
/*Banking*/
'GP_NET_PAY1_TMP', 'GP_NET_PAY2_TMP', 'GP_NET_PAY3_TMP',
'GP_NET_DST1_TMP', 'GP_NET_DST2_TMP',
'GP_PAYMENT_TMP', 'GP_PAYMENT2_TMP',
'GP_REV_DLTA_TMP', /*added 9.6.2004*/
'GP_SRC_BNK1_TMP', 'GP_SRC_BNK2_TMP',
/*Swiss Banking*/
'GPCH_BK_TMP1', 'GPCH_BK_TMP2',
'GPCH_BK_PMTTYPE',
/*reporting*/
'GPCH_BL_PRINT_T',
'GPCH_BL_PRT',
'GPCH_RP_AL1',

```

```

'GPCH_RP_AL01',
'GPCH_RP_AL03' , 'GPCH_RP_AL03_1',
'GPCH_RP_AL07_1', 'GPCH_RP_AL07_2', 'GPCH_RP_AL07_3',
'GPCH_RP_AL08',
'GPCH_RP_AL81' , 'GPCH_RP_AL82' , 'GPCH_RP_AL83',
'GPCH_RP_TX01A' ,
'GPCH_RP_TX06' , 'GPCH_RP_TX06_01',
'GPCH_RP_TX61' , 'GPCH_RP_TX62' , 'GPCH_RP_TX63',
'GPCH_RP_FK1A', 'GPCH_RP_FK2A',
'GPCH_RP_0001_01',
'GPCH_SRC_BNK',
'GPCHAL021_TMP', 'GPCHAL022_TMP', 'GPCHAL023_TMP',
'GPCHAL024_TMP',
'GPCHAL031_TMP',
'GPCHAL051_TMP', 'GPCHAL052_TMP',
'GPCHAL071_TMP', 'GPCHAL072_TMP', 'GPCHAL073_TMP', 'GPCHAL074_TMP', 'GPCHAL075_TMP',
'GPCHAL101_TMP', 'GPCHAL102_TMP',
'GPCHSI061_TMP',
'GPCHST021_TMP', 'GPCHST022_TMP', 'GPCHST023_TMP',
'GPCHTX011_TMP', 'GPCHTX012_TMP',
'GPCHTX021_TMP',
'GPCHTX061_TMP', 'GPCHTX062_TMP', 'GPCHTX063_TMP', 'GPCHTX064_TMP',
'GPGB_PSLIP_ED_D', 'GPGB_PSLIP_BL_D', /*gpgb_pslip can now be run stream 4.2.2004*/
'GPGB_PSLIP_ED_W', 'GPGB_PSLIP_BL_W',
--customer tables
...
)
OR r.recname IN(
SELECT t.recname30
FROM psaeappltemptbl t
, psaeappldefn a
WHERE a.ae_applid = t.ae_applid
AND a.ae_disable_restart = 'Y' --restart is disabled
AND a.ae_applid IN('GP_PMT_PREP', 'GP_GL_PREP'
, 'GPGB_PSLIP', 'GPGB_PSLIP_X', 'GPGB_EDI') /*limited to GP AE processes*/
))
/

```

³⁰ This subquery adds any records that are used as temporary working storage tables in the GP Application Engine programs that can be streamed and that have restart disabled.

```

-----
--insert data to specify the tables to be partitioned
--country specific tables for installed country extentions only will be added
-----

DELETE FROM gfc_part_tables
WHERE part_id = 'GP'
/

INSERT INTO gfc_part_tables
(recname, part_id, part_column, part_type)
SELECT r.recname, 'GP'
,      'EMPLID', 'R'
FROM   gfc_installed_gp r
WHERE  r.installed_gp != 'N'
AND    r.rectype = 0 --only normal tables can be partitioned
AND    (      r.recname IN(
                'GP_AUDIT_TBL',          /*added 21.5.2008*/
                'GP_ABS_EVENT',         /*absence - added 3.10.2003*/
                'GP_GL_DATA',           /*gl transfer table*/
                'GP_GRP_LIST_RUN',      /*new in 8.4*/
                'GP_ITER_TRGR',
                'GP_MESSAGES',
                'GP_PAYMENT',
                'GP_PI_GEN_HDR',        /*13.2.2008-added*/
                'GP_PI_GEN_DATA',       /*positive input*/
                'GP_PI_GEN_REF',        /*13.2.2008-added for kelly-TL positive input*/
                'GP_PI_GEN_SOVR',       /*14.11.2008-added*/
                'GP_PI_MNL_DATA',       /*positive input*/
                'GP_PI_MNL_SOVR',       /*positive input*/
                'GP_PYE_ITER_LST',      /*13.2.2008-added*/
                'GP_PYE_OVRD',
                'GP_PYE_PRC_STAT',
                'GP_PYE_SEG_STAT',
                'GP_RCP_PYE_DTL',       /*added 7.6.2004 for gp_pmt_prep*/
                'GP_RSLT_ABS',          /*payroll calculation results*/
                'GP_RSLT_ACUM',         /*payroll calculation results*/
                'GP_RSLT_DELTA',        /*payroll calculation results*/
                'GP_RSLT_ERN_DED',      /*payroll calculation results*/
                'GP_RSLT_PI_DATA',      /*payroll calculation results*/
                'GP_RSLT_PI_SOVR',      /*payroll calculation results*/
                'GP_RSLT_PIN',          /*payroll calculation results*/
                'GP_RTO_TRG_CTRY',      /*8.1 + 8.3 only*/
                'GP_RTO_TRGR',          /*deadlock problem*/
                'GPCH_BK_XFER_EE',      /*bank transfer*/
                'GPCH_TX_DATA',         /*tax data table - added 19.6.2003 - to improve scan and reduce
latch contention*/
                'GPGB_ABS_EVT_JR',
                'JOB',                  /*hr data */
                'COMPENSATION',         /*hr compensation data added 18.1.2010*/
                'X_PYE_OVRD_ET',        /*customer table*/
                'GPGB_PAYMENT',         /*added 12.3.2004*/
                'GPGB_PSLIP_P_ED',      /*uk payslip process gpgb_pslip can now be run streamed*/
                'GPGB_PSLIP_P_BL',      /*uk payslip process gpgb_pslip can now be run streamed*/
                'GPGB_PSLIP_P_HR',      /*uk payslip process gpgb_pslip can now be run streamed*/
                'GPGB_PSLIP_P_FT',      /*uk payslip process gpgb_pslip can now be run streamed*/
            )

```

```

                'TL_PAYABLE_TIME'          /*13.2.2008-added-TL*/
            )
    OR      r.recname IN(                    /*range partition any writable arrays*/
                SELECT  recname
                FROM    ps_gp_wa_array31
            )
    )
/

```

Sometimes, the easiest way to remove archived data from the payroll tables is to rebuild them, and exclude the unwanted data. A criterion can be specified for each table, and it gets added to INSERT ... SELECT command. Usually, this is left blank

```

-----
--process the filter column here
-----

UPDATE gfc_part_tables p
SET    p.criteria = ''
/

UPDATE gfc_part_tables p
SET    p.criteria = 'WHERE cal_run_id >= 'XX2008'''
WHERE EXISTS(
        SELECT  'x'
        FROM    psrecfield f
        WHERE   p.recname = f.recname
        and     f.fieldname IN('CAL_RUN_ID', 'SRC_CAL_RUN_ID', 'CAL_ID')
    )
AND p.criteria IS NULL
AND    1=2
;

UPDATE gfc_part_tables p
SET    p.criteria = ''
WHERE  p.recname IN('JOB', 'GP_ABS_EVENT', 'GPGB_ABS_EVT_JR')
;

tttitle 'Filter Conditions'
column recname format a18
column criteria format a60
SELECT  recname, criteria
FROM    gfc_part_tables
ORDER BY 1
/
tttitle off

```

³¹ In Global Payroll some results can be written to what PeopleSoft calls 'writable arrays'. These are separate database tables, and so should also be partitioned.

The two largest GP result tables are good candidates for list sub-partitioning by calendar group ID. Sometimes, other tables are possible candidates.

```

-----
--specify list subpartitioned tables
-----
UPDATE   gfc_part_tables
SET      subpart_type = 'L'
,        subpart_column = 'CAL_RUN_ID'
,        hash_partitions = 0
WHERE    recname IN('GP_RSLT_ACUM', 'GP_RSLT_PIN'
--, 'GP_GL_DATA' --not always worth subpartitioning
--, 'GP_PYE_SEG_STAT' -- subpartitioning does not always work well with retro queries
--, 'GP_PYE_PRC_STAT' -- subpartitioning does not always work well with retro queries
--, 'GP_RSLT_PI_SOVR', 'GP_RSLT_PI_DATA' --14.2.2008 removed
)
/

```

The storage options can be set keep only a small amount of free space on most of the result tables. However, experience has shown that GP_PYE_SEG_STAT needs about 15% free space because it is updated during the payroll calculation with status information.

```

-----
--set storage options on partitioned objects
-----
UPDATE   gfc_part_tables
SET      tab_tablespace = 'GPAPP' /*default PSFT tablespace*/
,        idx_tablespace = 'PSINDEX' /*default PSFT tablespace*/
,        tab_storage = 'PCTUSED 95 PCTFREE 1'
,        idx_storage = 'PCTFREE 1'
/

UPDATE   gfc_part_tables
SET      tab_storage = 'PCTUSED 80 PCTFREE 15'
WHERE    recname IN('GP_PYE_SEG_STAT')
/

```

Global Indexes

Not all indexes should be locally partitioned. This statement generates meta-data to suppress partitioning of the index if the partitioning key does not appear in the first three columns of the index. The result is a non-partitioned global index.

```

-----
--describe indexes that are not to be locally partitioned
-----

INSERT INTO gfc_part_indexes
(recname, indexid, part_id, part_type, part_column, subpart_type, subpart_column, hash_partitions)
SELECT  t.recname
,       i.indexid
,       t.part_id
,       t.part_type
,       t.part_column
,       'N' subpart_type
,       '' subpart_column
,       t.hash_partitions
FROM    gfc_part_tables t
,       psindexdefn i
WHERE   t.recname = i.recname
AND     t.subpart_type = 'L'
AND NOT EXISTS(
        SELECT 'x'
        FROM pskeydefn k, psrecfielddb f
        WHERE f.recname = i.recname
        AND   k.recname = f.recname_parent
        AND   k.indexid = i.indexid
        AND   k.fieldname = t.subpart_column
        AND   k.keyposn <= 3
        )
;

```

This is another example of an index that should not be partitioned. The meta-data is explicitly inserted.

```

INSERT INTO gfc_part_indexes
(recname, indexid, part_id, part_type, part_column)
VALUES
('TL_PAYABLE_TIME', 'A', 'GP', 'N', ' ')
/

```

Global Payroll Streams

In Global Payroll, the 'Streams' are defined as ranges of EMPLID in the table PS_GP_STRM. The meta-data that describes the range partitions for the payroll tables is derived directly from this table. Thus, once the streams have been defined, the partitioning will automatically match the stream definition, and there will be a 1:1 mapped of payroll process to physical table partition. Thus each block of each partition cannot be updated by more than one process at a time, and there is no possibility of consistent read having to be done by the database in payroll processes. The result is very good scalability of payroll with the number of streams.

```

-----
--insert data to specify range partitioning strategy
-----

DELETE FROM gfc_part_ranges
WHERE part_id = 'GP'
/

INSERT INTO gfc_part_ranges
(part_id, part_no, part_name, part_value)
SELECT  'GP', strm_num
,        LTRIM(TO_CHAR(strm_num,'000')) part_name
,        NVL(LEAD(''||emplid_from||',1) OVER (ORDER BY strm_Num),'MAXVALUE') part_value
FROM     ps_gp_strm
/

UPDATE   gfc_part_ranges32
SET      tab_tablespace = 'GPSTRM'||LTRIM(TO_CHAR(MOD(part_no-1,32)+1,'00'))||'TAB'
,        idx_tablespace = 'GPSTRM'||LTRIM(TO_CHAR(MOD(part_no-1,32)+1,'00'))||'IDX'
--SET    tab_tablespace = 'GPSTRM'||part_name||'TAB'
--,      idx_tablespace = 'GPSTRM'||part_name||'IDX'
--SET    tab_tablespace = 'GPTABPART'||part_name||''
--,      idx_tablespace = 'GPIDXPART'||part_name||''
--,      tab_storage = '/*TAB STORAGE*/'
--,      idx_storage = '/*IDX STORAGE*/'
WHERE 1=1
/

```

³² A pair of tablespaces is created for each payroll stream. All the tables for the same stream go into the same tablespace. There is no particular performance need for this, but it helps to determine how much I/O came from which stream.

Function Based Indexes

Sometimes, it will be necessary to build indexes that are not defined in PeopleSoft. A typical example is a function based index which cannot be defined in PeopleSoft.

```

-----
--insert data to generate the function based indexed
-----

--(recname,indexid,keyposn,fieldname)
INSERT INTO gfc_part_indexes (recname, indexid, part_id, part_type, part_column, idx_storage, name_suffix)
VALUES ('TL_PAYABLE_TIME','Y','GP','N',' ', 'PCTFREE 1','_SPARSE');33
INSERT INTO gfc_ps_indexdefn (recname, indexid, subrecname, subindexid, platform_ora, custkeyorder, uniqueflag)
VALUES ('TL_PAYABLE_TIME','Y','TL_PAYABLE_TIME','Y', 1, 0, 0);

--(recname,indexid,keyposn,fieldname)
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Y',1,'DECODE(PAYABLE_STATUS,'SP','SP',NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Y',2,'DECODE(PAYABLE_STATUS,'SP',EMPLID,NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Y',3,'DECODE(PAYABLE_STATUS,'SP',DUR,NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Y',4,'DECODE(PAYABLE_STATUS,'SP',EMPL_RCD,NULL)',1);

INSERT INTO gfc_part_indexes (recname, indexid, part_id, part_type, part_column, idx_storage, name_suffix)
VALUES ('TL_PAYABLE_TIME','Z','GP','L',' ', 'PCTFREE 1','_SPARSE');34
INSERT INTO gfc_ps_indexdefn (recname, indexid, subrecname, subindexid, platform_ora, custkeyorder, uniqueflag)
VALUES ('TL_PAYABLE_TIME','Z','TL_PAYABLE_TIME','Z', 1, 0, 0);

INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Z',1,'DECODE(PAYABLE_STATUS,'NA','NA',NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Z',2,'DECODE(PAYABLE_STATUS,'NA',EMPLID,NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Z',3,'DECODE(PAYABLE_STATUS,'NA',DUR,NULL)',1);
INSERT INTO gfc_ps_keydefn
VALUES ('TL_PAYABLE_TIME','Z',4,'DECODE(PAYABLE_STATUS,'NA',EMPL_RCD,NULL)',1);

```

³³ Index PSYTL_PAYABLE_TIME_SPARE will be created on table PS_TL_PAYABLE_TIME. The suffix is added to the index name to eliminate the risk that PeopleTools will attempt to drop it. This index will be a Global non-partitioned index.

³⁴ Index PSZTL_PAYABLE_TIME_SPARE will also be created on table PS_TL_PAYABLE_TIME. This index will be locally partitioned index.

This is the output generated

```
CREATE INDEX sysadm.psytl_payable_time_sparse ON sysadm.ps_tl_payable_time
(DECODE(PAYABLE_STATUS, 'SP', 'SP', NULL)
,DECODE(PAYABLE_STATUS, 'SP', EMPLID, NULL)
,DECODE(PAYABLE_STATUS, 'SP', DUR, NULL)
,DECODE(PAYABLE_STATUS, 'SP', EMPL_RCD, NULL)
)
TABLESPACE PSINDEX
...
CREATE INDEX sysadm.psztl_payable_time_sparse ON sysadm.ps_tl_payable_time
(DECODE(PAYABLE_STATUS, 'NA', 'NA', NULL)
,DECODE(PAYABLE_STATUS, 'NA', EMPLID, NULL)
,DECODE(PAYABLE_STATUS, 'NA', DUR, NULL)
,DECODE(PAYABLE_STATUS, 'NA', EMPL_RCD, NULL)
)
LOCAL
(PARTITION tl_payable_timez2008109 TABLESPACE GP2008L09IDX
...
, PARTITION tl_payable_timez2010113 TABLESPACE GP2010L13IDX
, PARTITION tl_payable_timezz_others
)
TABLESPACE PSINDEX
...
```

List Partitioning

The requirements for list partitions vary greatly from customer to customer. The insert statements do extract the calendar group names from the application tables because the calendars might not have been created at the time when the DBA needs to create the partitions.

Again, the following are examples collected from several sites.

```

-----
--insert data to list partitions
--2007 onwards
-----
DELETE FROM gfc_part_lists
WHERE part_id = 'GP'
/
INSERT INTO gfc_part_lists35
(part_id, part_no, part_name, list_value)
VALUES ('GP',9999,'Z_OTHERS','DEFAULT')
/
-----

--monthly partitions for Pensioners36
-----
INSERT INTO gfc_part_lists
(part_id, part_no, part_name, list_value)
SELECT  'GP'
,      year
,      LTRIM(TO_CHAR(y.year,'0000'))
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM01','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM02','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM03','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM04','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM05','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM06','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM07','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM08','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM09','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM10','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM11','||
,      ''||LTRIM(TO_CHAR(y.year,'0000'))||'PM12''
FROM (
SELECT  2007+rownum as year37
FROM    dba_objects
WHERE   rownum <= 3
) y

```

³⁵ There should always be a DEFAULT list partition. And rows for which the value of the list partitioning column does not match any other partition will go in here. If this was omitted, there would be a risk of an insert or update operation failing with an error, and crashing a process.

³⁶ One list partition per year. Each partition contains 12 calendar group IDs.

³⁷ Partitions will be created for 3 tax years starting with 2008-09.

```
ORDER BY 1,2,3
```

```
/
```

```
-----
--lunar monthly partitions for lunar and weekly38
-----

INSERT INTO gfc_part_lists
(part_id, part_no, part_name, list_value)
SELECT  'GP'
,       year+period/100
,       LTRIM(TO_CHAR(y.year,'0000'))||'L'||LTRIM(TO_CHAR(p.period,'00'))
,       ''''||LTRIM(TO_CHAR(y.year,'0000'))||'UL'||LTRIM(TO_CHAR( p.period , '00'))||''',''|
,       ''''||LTRIM(TO_CHAR(y.year,'0000'))||'UW'||LTRIM(TO_CHAR(4*p.period-3,'00'))||''',''|
,       ''''||LTRIM(TO_CHAR(y.year,'0000'))||'UW'||LTRIM(TO_CHAR(4*p.period-2,'00'))||''',''|
,       ''''||LTRIM(TO_CHAR(y.year,'0000'))||'UW'||LTRIM(TO_CHAR(4*p.period-1,'00'))||''',''|
,       ''''||LTRIM(TO_CHAR(y.year,'0000'))||'UW'||LTRIM(TO_CHAR(4*p.period-0,'00'))||''''
FROM    (
        SELECT  rownum as period
        FROM    dba_objects
        WHERE   rownum <= 14
        ) p
,
        (
        SELECT  2007+rownum as year
        FROM    dba_objects
        WHERE   rownum <= 3 --years of list partitions
        ) y
WHERE   period <= DECODE(y.year,2023,14,13)
ORDER BY 1,2,3
/

--need to add specific years where w53
UPDATE  gfc_part_lists a39
SET     a.list_value = a.list_value ||','||SUBSTR(a.part_name,1,4)||'UW53'''
WHERE   a.part_id = 'GP'
AND     a.part_name = (
        SELECT  MAX(b.part_name)
        FROM    gfc_part_lists b
        WHERE   a.part_id = 'GP'
        AND     SUBSTR(a.part_name,1,5) = SUBSTR(b.part_name,1,5))
AND     (a.part_name LIKE '2013_' OR
        a.part_name LIKE '2023_') -- and others
/
```

³⁸ Here, there will be 13 partitions per year, 14 in a lunar leap year. Each period will contain one period for lunar pay cycles, the 4 weekly calendar groups for the same period, and

³⁹ The 53rd weekly period will be added to the 13th partition for that year.

Selectively Building Sub-Partitions

It is not always necessary to build every list partition for every range partition.

```

-----
--mapping between ranges and lists
-----

DELETE FROM gfc_part_range_lists
WHERE part_id = 'GP'
/

INSERT INTO gfc_part_range_lists40
(part_id, range_name, list_name)
SELECT r.part_id, r.part_name, l.part_name
FROM   gfc_part_ranges r
,      gfc_part_lists l
WHERE  l.part_id = r.part_id
/

-----
--delete range/list combinations that are not needed
-----

DELETE FROM gfc_part_range_lists
WHERE build = 'Y'
AND   ( (list_name like 'IRL%' AND range_name != '01')41
        OR (list_name like 'UK%' AND NOT range_name IN('02','03','04','05','06','07','08'))42
AND   build = 'Y'
AND   part_id = 'GP'
/

--Uncomment this if you to just rebuild composite partitioned tables
--DELETE FROM gfc_temp_tables --WHERE RECNAME != ' '
--;
--DELETE FROM gfc_part_tables
--WHERE subpart_type = 'N'
--RECNAME != 'GP_PYE_SEG_STAT'
--;

```

⁴⁰ For ease of processing a table with ever combination of range and list is built, and then unwanted partitions will be marked.

⁴¹ Here the EMPLIDs of a company's Irish employees always fell into stream 1. So we don't want to build the list partitions for the Irish Calendar Group IDs in any stream other than stream 1. If we did they would be empty. The Irish payroll is not streamed, but it is still advantageous to have separate list sub-partitions for each period.

⁴² The UK employees are in streams 2 through 8, and not in stream 1, so there is no point having list partitions for UK calendar group IDs in stream 1.

Setting Context Values

The final part of the meta-data is to set site specific settings in the context via another public procedure in the *gfc_pspart* package (see SET_DEFAULTS Procedure on page 54).

```
-----  
--set gfc_pspart defaults  
-----  
  
set serveroutput on buffer 1000000000  
execute gfc_pspart.set_defaults(p_read_all=>'XXX_READ_ONLY');  
execute gfc_pspart.set_defaults(p_update_all=>'XXX_UPDATE');  
execute gfc_pspart.set_defaults(p_roles => 'Y');  
execute gfc_pspart.set_defaults(p_ddltrigger => 'T_LOCK');  
execute gfc_pspart.display_defaults;
```

Globally Partitioned Indexes

Globally partitioned indexes must have a MAXVALUE partition specified. So in this case the range partition definition for TL is copied to TLMAX, and a MAXVALUE partition is added.

```
--TLMAX is identical to TL but has maxvalue to support globally partitioned indexes  
INSERT INTO gfc_part_ranges  
(part_id, part_no, part_name, part_value, tab_tablespace, idx_tablespace)  
SELECT 'TLMAX', part_no, part_name, part_value, tab_tablespace, idx_tablespace  
FROM gfc_part_ranges  
WHERE part_id = 'TL'  
/  
  
INSERT INTO gfc_part_ranges  
(part_id, part_no, part_name, part_value)  
VALUES  
( 'TLMAX', 9999, 9999, 'MAXVALUE')  
/
```

Example Time & Labor Meta-Data

Archiving Time-Based Range Partitioning

```

UPDATE   gfc_part_tables
SET      arch_flag = 'A'43
,        arch_schema = 'PSARCH'44
WHERE    part_id IN('SCH')
OR       recname IN('AUDIT_SCH_TBL')
/

UPDATE   gfc_part_tables
SET      noarch_condition = 'sch_adhoc_ind = ''1'''45
WHERE    recname IN('SCH_DEFN_TBL','SCH_DEFN_DTL','SCH_DEFN_ROTATN','SCH_DEFN_SHFT')
/

```

```

INSERT INTO gfc_part_ranges
(      part_id, part_no, part_name, part_value, tab_tablespace, idx_tablespace, arch_flag)
SELECT y.part_id, y.part_no, y.part_name, y.part_value, t.tablespace_name, i.tablespace_name, y.arch_flag
FROM   (
  SELECT 'SCH' part_id
,       TO_NUMBER(TO_CHAR(mydate,'iyIW')) part_no
,       TO_CHAR(mydate,'iyIW') part_name
,       'TO_DATE('' ' || TO_CHAR(MAX(mydate)+1,'YYYYMMDD') || '' , ''YYYYMMDD'')' part_value
,       'TL' || TO_CHAR(MAX(mydate), 'YYYY') || 'M' || TO_CHAR(MAX(mydate), 'MM') || 'TAB' tab_tablespace
,       'TL' || TO_CHAR(MAX(mydate), 'YYYY') || 'M' || TO_CHAR(MAX(mydate), 'MM') || 'IDX' idx_tablespace
,       CASE WHEN MAX(mydate)+1 < ADD_MONTHS(SYSDATE, -12) THEN 'A' ELSE 'N' END arch_flag --46archiving
--      ,       CASE WHEN MAX(mydate)+1 < TO_DATE('20100101', 'yyyymmdd') THEN 'A' ELSE 'N' END arch_flag --
archiving
--      ,       CASE WHEN MAX(mydate)+1 < TO_DATE('20090101', 'yyyymmdd') THEN 'A' ELSE 'N' END arch_flag --
archiving
  FROM   (
    SELECT a.from_dt+b.n mydate
    from   (
      select TO_DATE('01102008', 'DDMMYYYY') from_dt
    from   dual

```

⁴³ Tables to be archived or purged by dropping partitions can be identified in the meta data.

⁴⁴ In this case the data will be moved to an archive table with the same name but in a different schema.

⁴⁵ Sometimes it is necessary to preserve data that would otherwise be removed by partition exchange. The NOARCH_CONDITION column can be used to hold the logical criteria to select data to be retained. GFC_PSPART does not use this directly, but the partition exchange package also uses the GFC_PSPART meta-data.

⁴⁶ The archive flag on GFC_PART_RANGES indicates which range partitions should be archived. Note that partitions will only be archived if both the GFC_PART_TABLES.ARCH_FLAG and GFC_PART_RANGES.ARCH_FLAG are set.

```
        ) a
    ,    (
        select rownum n
        from dual
        connect by level <= (SYSDATE-TO_DATE('20081107','yyyymmdd'))
        ) b
    ) x
WHERE mydate >= TO_DATE('20081107','yyyymmdd')
GROUP BY TO_CHAR(mydate,'iyIW')
HAVING MIN(mydate) < TO_DATE('20120501','yyyymmdd')
) y
left outer join dba_tablespaces t on t.tablespace_name = y.tab_tablespace
left outer join dba_tablespaces i on i.tablespace_name = y.idx_tablespace
ORDER BY 1,2,3
/
```

Meta-Data Report

Part of the partdata.sql script generates a report of the meta-data that contains a number of sections

Partitioned Tables

Thu Nov 26										page 1	
Partitioned Tables											
PeopleSoft		Part		Part SubP		Sub-Part		Hash Table		Index	
Record Name		Part ID Column		Type Type		Column		Parts TblSpc		TblSpc	

Table		Index		Stats		Sample Optimizati		Override			
Storage Clause		Storage Clause		Opt		Size % Method		Schema			

Criteria											

...											
GP_RSLT_ACUM		GP		EMPLID		R L		CAL_RUN_ID		0 GPAPP PSINDEX	
PCTUSED 95		PCTFREE 1		PCTFREE 1		Y					
...											
SCH_ADHOC_DTL		TL		DUR		R N		0 TLLARGE		PSINDEX	
INITRANS 4		PCTUSED 9		INITRANS 4		PCTFREE 0		Y			
0 PCTFREE 1											
...											

Range Partitioning

Thu Nov 26										page 1	
Range Partitioning											
Part ID		Part No. Name		Part Value		Table TblSpc		Index TblSpc			

Table		Index									
Storage Clause		Storage Clause									

GP		1.00 001		'KUL451'		GPSTRM01TAB		GPSTRM01IDX			
GP		2.00 002		'KUL452'		GPSTRM02TAB		GPSTRM02IDX			
GP		3.00 003		'KUL453'		GPSTRM03TAB		GPSTRM03IDX			
GP		4.00 004		'KUL454'		GPSTRM04TAB		GPSTRM04IDX			
...											
TL		1218.00 1218		TO_DATE('20120507','YYYYMMDD')							
...											
TLMAX		1218.00 1218		TO_DATE('20120507','YYYYMMDD')							
TLMAX		9999.00 9999		MAXVALUE							

List Partitioning

Thu Nov 26			page 1
List Partitioning			
Part ID	Part No.	Part Name	

List Value		Table	TblSpC

Index TblSpC	Table Storage Clause	Index Storage Clause	

GP	2008.01	2008L01	
'2008GL01', '2008GW01', '2008GW02', '2008GW03', '2008GW04', '2008UL01', '2008UW01', '2008UW02', '2008UW03', '2008UW04', '2008AA01', '2008AA02', '2008AA03'			
GP2008L01TAB			
GP2008L01IDX			
GP	2008.02	2008L02	
'2008GL02', '2008GW05', '2008GW06', '2008GW07', '2008GW08', '2008UL02', '2008UW05', '2008UW06', '2008UW07', '2008UW08', '2008AA05', '2008AA06', '2008AA07'			
GP2008L02TAB			
GP2008L02IDX			
...			

Global and Globally Partitioned Indexes

Thu Nov 26 page 1

Non-Locally Partitioned Indexes

PeopleSoft Record Name	IND	Part	Part ID Column	Part SubP Type	Sub-Part Column	Hash Index Parts TblSpC

Index		Override				
Storage Clause		Schema				

TL_PAYABLE_TIME	A	GP		N	N	
TL_PAYABLE_TIME	C	GP		N	N	
TL_PAYABLE_TIME	D	GP		N	N	
TL_PAYABLE_TIME	E	GP		N	N	
TL_PAYABLE_TIME	F	TLMAX	DUR	R	N	
COMPRESS 1 ⁴⁷						

Specified Tablespaces

It is useful to be able to tell the DBAs which tablespaces are required.

Thu Nov 26 page 1

Specified Tablespaces

Table PAR TblSpC	Index TblSpC

GPAPP	PSINDEX
TLAPP	PSINDEX
TLLARGE	PSINDEX
...	
L GP2008L01TAB	GP2008L01IDX
L GP2008L02TAB	GP2008L02IDX
...	
R GPSTRM01TAB	GPSTRM01IDX
R GPSTRM02TAB	GPSTRM02IDX
R GPSTRM03TAB	GPSTRM03IDX
R GPSTRM04TAB	GPSTRM04IDX
...	

⁴⁷ Note that globally partitioned indexes must have an unlimited upper range, so the last value must use a MAXVALUE operator.

This section lists the tablespaces that are referenced in the meta data, and that have not been built.

Thu Nov 26	Tablespaces to be created	page 1
Table		
TblSpc		

GP2008L01IDX		
GP2008L01TAB		
GP2008L02IDX		
GP2008L02TAB		

Package GFC_PSPART

The GFC_PSPART contains a number of public procedures that can be called.

BANNER Procedure

This procedure prints the copyright message.

Syntax

```
gfc_pspart.banner;
```

There are no parameters to this procedure.

```
GFC_PSPART - Partitioned/Global Temporary Table DDL generator for PeopleSoft  
(c)Go-Faster Consultancy Ltd. www.go-faster.co.uk 2001-2009
```

NB: This procedure outputs via DBMS_OUTPUT. You will need to *set serveroutput on* in SQL*Plus to obtain any output.

DISPLAY_DEFAULTS Procedure

This procedure prints the value of all the parameters in the system context (see page 22).

Syntax

```
gfc_pspart.display_defaults;
```

There are no parameters to this procedure.

```
GFC_PSPART - Partitioned/Global Temporary Table DDL generator for PeopleSoft  
(c)Go-Faster Consultancy Ltd. www.go-faster.co.uk 2001-2009
```

PACKAGE DEFAULTS

```
Character VARCHAR2 definition          : N  
Rebuild tables with redo logging       : N  
Enable parallelism for table copy     : N  
Enable parallel index build           : Y  
Grant privileges to roles              : N  
Name of update all role                 : PS_UPDATE_ALL  
Name of select all role                 : PS_READ_ALL  
ID Prefix in files and project         : GFCBUILD  
Drop indexes                           : Y  
Pause commands in build script        : N  
Explicitly specify schema              : Y  
Block sample table statistics          : Y  
Analyze table immediately after rebuild: N  
Delete and lock statistics on GTTS     : Y  
Force LONGS to CLOBS                  : N  
Name of DDL trigger to disable on build:  
Drop tables with PURGE option          : Y  
Force rebuild if no change             : Y  
Force descending index                 : Y
```

NB: This procedure outputs via DBMS_OUTPUT. You will need to *set serveroutput on* in SQL*Plus to obtain any output.

HISTORY Procedure

This procedure lists the change history to the package.

Syntax

```
gfc_pspart.history;
```

There are no parameters to this procedure.

```
GFC_PSPART - Partitioned/Global Temporary Table DDL generator for PeopleSoft
(c)Go-Faster Consultancy Ltd. www.go-faster.co.uk 2001-2009
03.12.2002 - improved subrecord handling
11.02.2003 - correction to column sequencing on user
09.07.2003 - nologging facility added
10.07.2003 - oracle version detection added to control fix for 8.1.7.2 bug
05.09.2003 - corrected handling of peoplesoft long character columns
18.09.2003 - added trigger to prevent updates on tables whilst being rebuilt
09.10.2003 - tables and indexes set to logging enabled and parallel disabled,
parallel control variable added
28.10.2003 - supress partitioning for tables with long columns
29.10.2003 - pt version detection to enable new PT8.4 features
04.11.2003 - oracle 9i features, role name control
17.11.2003 - rename/drop index
07.01.2004 - explicit schema name, script control
22.03.2004 - oracle 9 varchars in characters
27.09.2004 - suppress disabled index build, but force disabled index to drop
18.04.2005 - support for PeopleSoft temporary tables
05.12.2006 - added handling for hash-partitioned only tables
13.12.2006 - remove partitioning column check
06.09.2007 - enhancement for PeopleTools 8.48, support partitioned function based indexes
08.11.2007 - support for range-list composite partitioning
14.02.2008 - selective list partition -v- range build, drop purge, all keys on subrecords
28.08.2008 - conversion to package procedure
16.09.2008 - DDL moved to gfcbuildtab
16.12.2008 - Single table build options can be combined
23.01.2009 - Partitioning columns in unique indexes must not be descending
01.04.2009 - Corrections to add partition scripts
18.04.2009 - Override Default Application Designer Project Name
03.06.2009 - Extended check descending partitioning columns in unique indexes to subrecords
23.04.2010 - Add ability to add range partitions by splitting
01.05.2010 - Correct setting new table LOGGING NOPARALLEL
05.05.2010 - Create table only if doesn't exist, add COLUMNS when altering table
17.05.2010 - Temporary Record that are not declared to any AE can be GTT
08.06.2010 - Specified Source Table
16.06.2010 - Function Based Index support enhanced
01.10.2010 - Insert into copy table within PL/SQL block
02.10.2010 - Optionally reenale parallelism on existing table prior to copy
```

NB: This procedure outputs via DBMS_OUTPUT. You will need to *set serveroutput on* in SQL*Plus to obtain any output.

RESET_DEFAULTS Procedure

This procedure resets the variables in the system context back to their default values (see page 22).

Syntax

```
gfc_pspart.reset_defaults;
```

There are no parameters to this procedure.

SET_DEFAULTS Procedure

This procedure permits one or more variables in the system context to be set. This values are persistent.

Syntax

```
gfc_pspart.set_defaults(  
(p_chardef          VARCHAR2 DEFAULT ''  
,p_logging          VARCHAR2 DEFAULT ''  
,p_parallel_table   VARCHAR2 DEFAULT ''  
,p_parallel_index   VARCHAR2 DEFAULT ''  
,p_roles            VARCHAR2 DEFAULT ''  
,p_scriptid         VARCHAR2 DEFAULT ''  
,p_update_all       VARCHAR2 DEFAULT ''  
,p_read_all         VARCHAR2 DEFAULT ''  
,p_drop_index       VARCHAR2 DEFAULT ''  
,p_pause            VARCHAR2 DEFAULT ''  
,p_explicit_schema  VARCHAR2 DEFAULT ''  
,p_block_sample     VARCHAR2 DEFAULT ''  
,p_build_stats      VARCHAR2 DEFAULT ''  
,p_deletetempstats VARCHAR2 DEFAULT ''  
,p_longtoclob       VARCHAR2 DEFAULT ''  
,p_ddltrigger       VARCHAR2 DEFAULT '*'  
,p_drop_purge       VARCHAR2 DEFAULT ''  
,p_forcebuild       VARCHAR2 DEFAULT ''  
,p_desc_index       VARCHAR2 DEFAULT ''  
,p_repopdf1tsub    VARCHAR2 DEFAULT ''  
,p_debug_level      INTEGER DEFAULT NULL  
);
```

Parameters

Parameter	Description
p_chardef	Y = Use VARCHAR2 character length definition.
p_logging	N = DDL script includes NOLOGGING options when building tables and indexes
p_parallel_table	Y = set default parallelism on existing table prior to copy
p_parallel_index	Y = include parallel index build option
p_roles	Y= if roles are to be granted to tables
p_scriptid	ID string to be used in name of script and name of project generated.
p_update_all	Name of Role to be granted to permanent tables
p_read_all	Name Role to be granted to permanent tables
p_drop_index	Y = index dropped before rename, N = index is renamed to OLD_
p_pause	Y = Add pause commands to generated script
p_explicit_schema	Explicitly specify PeopleSoft owner ID in DDL script.
p_block_sample	Specify block sampling in update statistics script.
p_build_stats	Y = add gather statistics commands to build script.
p_deletetempstats	Y = delete and from Oracle 10g also lock statistics on temporary tables.
p_longtocab	Y = always create long columns as CLOB, Otherwise only do so if PSOPTION.DATABASE_OPTIONS=2
p_ddltrigger	Name of DDL trigger to disable at start of script and reenale on completion.
p_drop_purge	Y = Add purge option to DROP TABLE commands on Oracle 10g or higher.
p_forcebuild	Debug option only – not supported
p_desc_index	Y include DESC keyword on columns specified in PeopleSoft as descending N = never use DESC keyword in CREATE INDEX commands.
p_repopdfitsub	N = exchange default list partition back into partitioned table when adding list sub-partitions Y = create new default list partition after adding new list sub-partitions and then copy the data back into the partitioned table from the exchange

	table.
--	--------

p_debug_level	0 = off. Higher values add more debug information. Only to be used on advice from Go-Faster Consultancy Ltd.
---------------	--

TRUNCATE_TABLES Procedure

This procedure clears out the working storage and meta-data tables

Syntax

```
gfc_pspart.truncate_tables
(p_all BOOLEAN DEFAULT FALSE
);
```

Parameters

Parameter	Description
p_all	<p>If true, all the working storage tables and meta-data tables are truncated. Otherwise, only the working storage tables are truncated.</p> <p>The meta-data tables only need to be truncated when different or new meta-data is being inserted.</p>

SPOOLER Function

This function can be used to spool

Syntax

```
TYPE outrecset IS TABLE OF VARCHAR2(200);
FUNCTION spooler
(p_type NUMBER DEFAULT 0)
RETURN outrecset PIPELINED;
```

Parameters

Parameter	Description
p_type	0 = gfcbuild script. Similar to a PeopleSoft Alter by Recreation script
	1 = gfcindex: Rebuild All indexes
	2 = gfcstats: Refresh All statistics
	3 = gfcalter: All missing partitions
	4 = gfcarch1: Build archive tables (possibly in a different schema to the main PeopleSoft database)
	5 = gfcarch2: Grant privileges on PeopleSoft tables to archive schema

Example

```
rem gfcbuildspool.sql
rem (c) Go-Faster Consultancy Ltd.
rem 17.9.2008 - moved spool commands from gfcbuild.sql to this script

column line format a254
set head off feedback off echo off verify off pages 0 lines 1024 trimspool on
set termout off

column SPOOL_FILENAME new_value SPOOL_FILENAME
select LOWER('gfcbuild_'||MAX(dbname)||'.sql') SPOOL_FILENAME from ps.psdowner where
UPPER(ownerid) = user;
spool &&SPOOL_FILENAME
undefine SPOOL_FILENAME
select * from table(gfc_pspart.spooler(0));
spool off
...
```

MAIN Procedure

The main procedure generates all the DDL for all the tables specified. The three parameters specific tables or groups of tables, so that only a subset of the records specified in the meta-data can be built.

Syntax

```
gfc_pspart.display_defaults
(p_recname      VARCHAR2 DEFAULT ''
,p_rectype      VARCHAR2 DEFAULT 'A'
,p_projectname  VARCHAR2 DEFAULT ''
);
```

Parameters

Parameter	Description
p_recname	Name of record to be generated. A simple pattern string may be specified as would be used with the LIKE operator.
p_rectype	P = Partitioned Tables only T = Global Temporary Tables only A = All tables, both Partitioned and Global Temporary. Default value is A
p_projectname	The name of an Application Designer project can be specified, and then only the records in the project will be built. Use this option when an upgrade project is being applied and you want to build just the tables in the project.